

# HYPOXIS MLS SL

## SAE 0W/30

FULL SYNTHETIC ENGINE OIL SL/CF

**DYADE**  
LUBRICANTS

320100501



### FULL SYNTHETIC ENGINE OIL SL/CF

This is a full synthetic engine oil that has initially been developed for Volvo passenger cars. It was specifically developed for the Volvo 5-cylinder engines. But the formulation of this product is also very suitable for the broader car portfolio and can be used for passenger cars, sports utility vehicles, vans and light trucks that are operating under the API SL specification. The specification A5/B5 on this product ensures that this product performs very well in engines that are designed using Low Viscosity Oils with HTHS Viscosities of 2.9 to 3.5 mPa\*s. This product can be use in gasoline as well as diesel engines.

### FUEL ECONOMY RATING



### SPECIFICATIONS

ACEA A5 / B5	BMW LONGLIFE-01 FE
API SL / CF	VOLVO VCC 95200377

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,85
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	55,2
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	10,3
Viscosity Index	ASTM D2270		178
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,09

## Product information

People buy this product because they need a high-quality low viscosity 0W/30 Engine Oil.

### CATEGORY

- Passenger Car
- Engine Oil

### BASE OIL

- Full Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

