

GYNURA TLD SM

SAE 5W/40

FULL SYNTHETIC ENGINE OIL SM

DYADE
LUBRICANTS

320100601



FULL SYNTHETIC ENGINE OIL SM

This product is a high quality full synthetic long-life engine oil that is recommended for all petrol engines with or without catalytic converter. It can also be used in diesel engines, turbocharged or naturally aspirated cars and light vans. This product is designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This product has the API SM specification but can also be used where older API specifications are applicable like SJ and SL.

Product information

People buy this product because it can be used for the more modern car fleet, diesel as well as gasoline.

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B3-16	FIAT 9.55535-Z2	RENAULT RN 0700
ACEA A3 / B4	MB 226.5	RENAULT RN 0710
API CF	MB 229.3	VW 502.00
API SM	OPEL GM-LL-A-025	VW 505.00
BMW LONGLIFE-01	OPEL GM-LL-B-025	
FIAT 9.55535-H2	PORSCHE A40	
FIAT 9.55535-M2	PSA B71 2296	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,856
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	86
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,4
Viscosity Index	ASTM D2270		175
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9,6
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,2

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM