

GYNURA TLD SM

SAE 10W/40

SEMI-SYNTHETIC ENGINE OIL SM

DYADE
LUBRICANTS

320100701



SEMI-SYNTHETIC ENGINE OIL SM

This product is a high quality semi-synthetic long-life engine oil. This product can be used for the lubrication of all 4-Stroke gasoline and diesel engines, which makes it perfect oil for the whole fleet. It is also suitable for vehicles that operate with a direct fuel injection. The total engine protection of this lubricant ensures outstanding engine cleanliness and it is very suitable for cold starts and Start-Stop traffic. This product has the API SM specification but can also be used where older API specifications are applicable like SJ and SL.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B3-16	MB 226.5	RENAULT RN 0710
ACEA A3 / B4	MB 229.1	VW 501.01
API SM	MB 229.3	VW 505.00
FIAT 9.55535-D2	MB 229.3	
FIAT 9.55535-G2	PSA B71 2300-2022	
LADA LADA-AVTOVAZ	RENAULT RN 0700	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,868
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	95,4
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,1
Viscosity Index	ASTM D2270		152
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1

Product information

People buy this product because it can be used for the more modern car fleet, diesel as well as gasoline.

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

