

HYPOXIS MLS SL SAE 10W/40

SEMI-SYNTHETIC ENGINE OIL SL/CF

DYADE
LUBRICANTS

320100901



SEMI-SYNTHETIC ENGINE OIL SL/CF

This engine oil is made of semi-synthetic base oils. It contains of extremely well formulated additive packages. This product can be used in vehicles where the EURO 4 norm is needed. It is suitable for gasoline and diesel vehicles that are in need of the API SL specification or older. This oil can be used for direct injection such as Common Rail, HDI, CDI, etc. Also this oil can be used in supercharged vehicles. This product has a very high resistance against oxidation, ensures engine protection and meets a variety of specifications.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B3-16	FIAT 9.55535-G2	VW 501.01
ACEA A3 / B4	MB 229.1	VW 505.00
API SL / CF	RENAULT RN 0700	
FIAT 9.55535-D2	RENAULT RN 0710	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0.866
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	91
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,8
Viscosity Index	ASTM D2270		155
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1

Product information

People buy this product because it is an excellent extended drain interval oil

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

