

HYPOXIS MLS SL SAE 15W/40

MULTI GRADE ENGINE OIL SL/CF

DYADE
LUBRICANTS

320101001



MULTI GRADE ENGINE OIL SL/CF

This engine oil is made of mineral base oils. It contains of extremely well formulated additive packages. It is suitable for gasoline and diesel vehicles that are in need of the API SL specification or older. This oil can be used for direct injection such as Common Rail, HDI, CDI, etc. Also this oil can be used in supercharged vehicles. This product has a very high resistance against oxidation, ensures engine protection and meets a variety of specifications.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B3-16	FIAT 9.55535-G2	RENAULT RN 0710
ACEA A3 / B4	MB 229.1	VW 501.01
API SL / CF	PSA B71 2295	VW 505.00
FIAT 9.55535-D2	RENAULT RN 0700	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,885
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	103
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,7
Viscosity Index	ASTM D2270		130
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	230
Sulphated ash content	ASTM D874	%	1,03

Product information

People buy this product because it is an excellent extended drain interval oil

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

