

# HYPOXIS MLS SL

## SAE 5W/30

FULL SYNTHETIC ENGINE OIL SL/CF

**DYADE**  
LUBRICANTS

320101101



### FULL SYNTHETIC ENGINE OIL SL/CF

This engine oil is made of full synthetic base oils. The full synthetic technology in this engine oil is several times more able to effectively remove sludge and dirt from engines than a mineral oil. It consists of extremely well formulated additive packages. It is suitable for gasoline and diesel vehicles that need the API SL specification or older. This oil is also particularly suitable for four-valve and turbo diesel engines with or without turbo. This product has a very high resistance against oxidation, ensures engine protection and meets a variety of specifications. One of the reasons why this product is extremely suitable for also the more modern car portfolio is its engine cleanliness properties and its additive package that ensures extended oil drain intervals and fuel saving.

### FUEL ECONOMY RATING



### SPECIFICATIONS

ACEA A3 / B4	OPEL GM-LL-A-025	VW 505.00
API SL / CF	OPEL GM-LL-B-025	
MB 229.1	VW 502.00	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0.858
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	66
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	11,1
Viscosity Index	ASTM D2270		162
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10
Pour point	ASTM D6892	°C	-42
Flash point	ASTM D92	°C	214
Sulphated ash content	ASTM D874	%	1

## Product information

People buy this product because it is an excellent extended drain interval oil

### CATEGORY

- Passenger Car
- Engine Oil

### BASE OIL

- Full Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

