

HYPOXIS MLS SL

SAE 20W/50

MULTI GRADE ENGINE OIL SL/CF

DYADE
LUBRICANTS

320101401



MULTI GRADE ENGINE OIL SL/CF

This engine oil is made of mineral base oils. It contains of extremely well formulated additive packages. It is suitable for gasoline and diesel vehicles that are in need of the API SL specification or older. This oil is also particularly suitable for four-valve and turbo diesel engines with or without turbo. This product has a very high resistance against oxidation, ensures engine protection and meets a variety of specifications. One of the reasons why this product is extremely suitable for also the more modern car portfolio is its engine cleanliness properties and its additive package that ensures extended oil drain intervals and fuel saving.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B3-16	MB 229.1	VW 505.00
ACEA A3 / B4	PSA B71 2295	
API SL / CF	VW 501.01	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0.89
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	155
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	18
Viscosity Index	ASTM D2270		125
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-24
Flash point	ASTM D92	°C	235
Sulphated ash content	ASTM D874	%	1.03

Product information

People buy this product because it is an excellent extended drain interval oil

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM