LARIX MED SN SAE OW/40

FULL SYNTHETIC ENGINE OIL SN/CF





FULL SYNTHETIC ENGINE OIL SN/CF

This product is a very advanced full synthetic engine oil that has been developed for gasoline and diesel engines. The full synthetic technology in this engine oil is several times more able to effectively remove sludge and dirt from engines then a mineral oil. This product ensures that your engine is driving like new in all driving conditions. This product has a very rapid engine protection start up, which makes it perfect for short distance driving and start-stop driving. Also the specifically designed additive package ensures that dirty engines are cleaned tremendously. This product is very suitable for engines that include turbo-chargers, direct injections diesels and Hybrids. Please note that this product is not suitable for vehicles with DPF filters.

FUEL ECONOMY RATING



CDECIFICATIONS

| OF ECH TOATTONS | | |
|-------------------|-----------------|-----------------|
| ACEA A3 / B4 | MB 226.5 | RENAULT RN 0710 |
| API SN | MB 229.3 | VW 502.00 |
| BMW LONGLIFE-01 | MB 229.5 | VW 505.00 |
| FIAT 9.55535-Z2 | PORSCHE A40 | |
| FORD WSS-M2C937-A | RENAULT RN 0700 | |
| | | |

| GRADE | METHOD | UNIT | VALUE | |
|------------------------------|------------|----------|-------|--|
| Density | ASTM D4052 | kg/l | 0,844 | |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm²/s | 80,1 | |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm²/s | 13,8 | |
| Viscosity Index | ASTM D2270 | | 178 | |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | 10,1 | |
| Pour point | ASTM D6892 | °C | -57 | |
| Flash point | ASTM D92 | °C | 220 | |
| Sulphated ash content | ASTM D874 | % | 1,09 | |



Product information

People buy this product because they want a high quality OW/40 oil with excellent Fuel Economy properties.

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

