MALVA EFE **SAE 0W/20** FUEL ECONOMY ENGINE OIL GF-5



FUEL ECONOMY RATING

320102201

FUEL ECONOMY ENGINE OIL GF-5

Today's engines are smaller, more efficient, more advanced and more powerful. Because of this, these engines need to operate in more extreme conditions. If not good protected by good oil, the cylinder walls, pistons, piston rings, connecting rods and spark plugs can cause permanent damage. This product has been formulated with sophisticated European base oils and additives that prevent this from happening. This is a full synthetic engine oil that we have specifically formulated for consumers that would like to experience an extreme high level of fuel economy in their gasoline passenger car, SUV, van or light truck. This all year round oil is developed in order to meet the challenging requirements of fuel efficient combustion vehicles as well as hybrid vehicles where CO2 reduction is very important. Also this product its very low viscosity ensures that it significantly reduces wear. soot ad deposits and keeps the engine clean.

Product information

LUBRICANTS

People buy this product because of its ILSAC GF-5 specification in gasoline cars and Hybrid vehicles.

CATEGORY

📕 Passenger Car Engine Oil

BASE OIL

Full Synthetic

AVAILABLE PACKAGING



SPECIFICATIONS

ACURA -	CHRYSLER MS 6395		
API SN PLUS	DODGE -		
API SN / RC	FIAT 9.55535-CR1		
API SP	FIAT 9.55535-GSX		
API SP / RC	FORD WSS-M2C945-A		
BUICK -	FORD WSS-M2C946-A		
CADILLAC -	FORD WSS-M2C947-A		
CHEVROLET -	FORD WSS-M2C962-A		

GM DEXOSI™ GEN 3 GMC -ILSAC GF-5 ILSAC GF-6 A JEEP .

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,849
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	45,6
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	8,69
Viscosity Index	ASTM D2270		173
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,1
Pour point	ASTM D6892	٦°	-48
Flash point	ASTM D92	٦°	222
Sulphated ash content	ASTM D874	%	0,88

MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE



DYADE LUBRICANTS B.V TYPOGRAAF 16 | 6921 VB DUIVEN

C 0031 (0) 316 745 745 INFO@DYADE-LUBRICANTS.COM

WWW.DYADEGLOBAL.COM