

# PYRUS DEX C2-C3

## SAE 5W/30

MID SAPS ENGINE OIL C2-C3

**DYADE**  
LUBRICANTS

320103101



### MID SAPS ENGINE OIL C2-C3

This product is a full synthetic lubricant for gasoline and diesel engines in passenger cars, light vans and trucks, and is part of our MID SAPS product range. The reduced ash formulation in this engine oil protects particle filters and exhaust after-treatment devices. This product meets the dexos 2™ approval that is needed for all GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. This specification is backwards compatible and can also be used in vehicles that describe GM-11-A-025 and GM-B-11-025. This product meets all requirements of the ACEA C2. This means that this engine oil is intended for use as catalyst compatible oil at extended drain intervals in vehicles with all types of modern aftertreatment systems and high performance passenger cars, light duty van gasoline and diesel engines that are designed to be capable of using low viscosity oils with a minimum HTHS viscosity of 2.9 mPa\*s.

### FUEL ECONOMY RATING



### SPECIFICATIONS

ACEA C2	GM DEXOS 2	OPEL GM-LL-B-025
ACEA C3	GM DEXOS1™ GEN 2	OPEL OV 040 1547 - D30
API SN PLUS	HYUNDAI .	OPEL OV 040 1547 - G30
API SP	IVECO 18-1811 CLASSE SCI	RENAULT RN 0700
BMW LONGLIFE-04	KIA .	RENAULT RN 0710
CHRYSLER MS 11106	MB 229.31	VW 505.01
FIAT 9.55535-S1	MB 229.51	VW 505.00
FIAT 9.55535-S3	MB 229.52	
FORD WSS-M2C917-A	OPEL GM-LL-A-025	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	67,1
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	12,2
Viscosity Index	ASTM D2270		182
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,2
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	234
Sulphated ash content	ASTM D874	%	0,77

## Product information

People buy this product because they need a MID SAPS C2 engine oil with the Dexos 2™ specification.

### CATEGORY

- Passenger Car
- Engine Oil

### BASE OIL

- Full Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADE-LUBRICANTS.COM  
WWW.DYADEGLOBAL.COM