PYRUS EXT C2-C3 SAE OW/30

MID SAPS ENGINE OIL C2-C3



320103201



FUEL ECONOMY RATING

MID SAPS ENGINE OIL C2-C3

This is a full synthetic engine oil that can be used in petrol as well as diesel engines. One of the big advantages of this motor oil is that it can obtain a significant fuel economy result compared to other more standard engine oils. This product has specifically been formulated for the BMW group passenger car vehicles, but can also be used in other vehicles that require a high quality 0W30 fuel economy engine oil. The BMW LL-04 specification on this product means that BMW approved it for fully synthetic long life engine oils. They can be used in vehicles that are equipped with a diesel particle filter (DPF). Note that this product can also be used in vehicles that require an older specification: BMW LL-01 & BMW LL-98. The formulation of this product also meets the Mercedes Benz MB 339.31 specification which means that it at least realizes a 1% fuel saving on used fuel in the M111 Fuel economy



SPECIFICATIONS

| ACEA C2 | BMW LONGLIFE-04 | MB 229.51 |
|------------|------------------|-----------|
| ACEA C3 | FIAT 9.55535-DS1 | |
| APLSN / CF | FIAT 9 55535-GS1 | |

| GRADE | METHOD | UNIT | VALUE | |
|------------------------------|------------|----------|-------|--|
| Density | ASTM D4052 | kg/l | 0,852 | |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm²/s | 66,6 | |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm²/s | 12,1 | |
| Viscosity Index | ASTM D2270 | | 182 | |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | 7,8 | |
| Pour point | ASTM D6892 | °C | -54 | |
| Flash point | ASTM D92 | °C | 224 | |
| Sulphated ash content | ASTM D874 | % | 0,8 | |
| | | | | |

Product information

People use this product because they are in need of a Fuel Saving engine oil with the BMW LL-04 specification

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

