

# LUBRICANTS





# **PAO TECHNOLOGY ENGINE OIL**

This is a full synthetic engine oil that is formulated with our PAO (Poly Alpha Olefin) technology. This product is suitable for passenger cars equipped with gasoline, diesel and LPG engines and that have after treatment devices and diesel particle filters. The PAO base oils used in this formulation ensure excellent low temperature fluidity, oxidation stability and thermal stability. The PAO synthetic base stocks offer low volatility required to perform the harshest temperatures. This product has exceptional properties compared to normal full synthetic engine oils and meets a variety of specifications. This product can be used perfectly in applications that are in need of demanding properties like racing and sporty driving.

## **FUEL ECONOMY RATING**



# **SPECIFICATIONS**

ACEA C2	GM DEXOS2™	OPEL OV 040 1547 - G30
ACEA C3	MB 229.31	PORSCHE C30
API SN PLUS	MB 229.51	VW 503.01
API SP	MB 229.52	VW 504.00 / 507.00
BMW LONGLIFE-04	OPEL GM-LL-A-025	
FIAT 9.55535-S3	OPEL GM-LL-B-025	
GM DEXOSI™ GEN 2	OPEL OV 040 1547 - D30	

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,853	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	70	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	11,6	
Viscosity Index	ASTM D2270		161	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,3	
Pour point	ASTM D6892	°C	-39	
Flash point	ASTM D92	°C	230	
Sulphated ash content	ASTM D874	%	0,7	

# **Product information**

People buy this product because they need an excellent PAO based full synthetic 5W30 engine oil

## **CATEGORY**

- Passenger Car
- Engine Oil

# BASE OIL

Full Synthetic

# **AVAILABLE PACKAGING**

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

