LARIX MED SN-X SAE 5W/40



320105201



FULL SYNTHETIC ENGINE OIL SN/CF

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation, specially developed to satisfy the most severe engine builders' requirements. It is formulated with non-conventional base oils and advanced additives. This engine oil can generally be used in gasoline engines of passenger cars, meeting the highest performance levels. Diesel engines of passenger cars with turbo and direct fuel injection. Extended drain intervals are possible, according to the specific OEM prescriptions. This oil is not suitable for diesel engines, that are equipped with a diesel particulate filter (DPF).

Product information

People buy this product because they need an engine oil API SN

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B3-16	FIAT 9.55535-N2	PSA B71 2296
ACEA A3 / B4	FIAT 9.55535-Z2	RENAULT RN 0700
API SN / CF	MB 226.5	RENAULT RN 0710
BMW LONGLIFE-01	MB 229.3	VW 502.00
CHRYSLER MS 12991	MB 229.5	VW 505.00
FIAT 9.55535-H2	OPEL GM-LL-B-025	
FIAT 9.55535-M2	PORSCHE A40	

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,857	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	83,3	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	13,8	
Viscosity Index	ASTM D2270		170	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,1	
Pour point	ASTM D6892	°C	-45	
Flash point	ASTM D92	°C	228	
Sulphated ash content	ASTM D874	%	1,1	
· · · · · · · · · · · · · · · · · · ·				

