

GYNURA TLD SM

SAE 0W/30

FULL SYNTHETIC ENGINE OIL SM

DYADE
LUBRICANTS

320105301



FULL SYNTHETIC ENGINE OIL SM

This is a full synthetic engine oil that offers excellent fluidity at low temperatures. A result of this is that this product can be used perfectly in engines that have start-stop mechanisms or vehicles that are used for short-distance driving. This product can be used in all 4-stroke engines, four-valve, turbocharges, and 4-stroke diesel engines with or without turbo. Please note that this product is not suitable in vehicles that have diesel particle filters.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B4	MB 229.3	VW 502.00
API SN / CF	RENAULT RN 0700	VW 505.00
BMW LONGLIFE-01	RENAULT RN 0710	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,844
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	66
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	11,9
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,1
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,1

Product information

People buy this product because they need an all-round API SM engine oil

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

