PYRUS EMS C2 FRD SAE OW/30

MID SAPS ENGINE OIL C2





MID SAPS ENGINE OIL C2

This is a full synthetic engine oil that has been developed for the EURO 6 TDCI Duratorg engines in ford engines after 2004. This product includes one of the latest technology Viscosity Index Improvers. This ensures that this product lasts very long before it needs oil changes. This product is developed for mandatory use in the newest EURO 6 TDCI Duratorg Ford engines. this product is also usable for other passenger car engines requiring a 0W30 viscosity grade and the ACEA C2 performance. This product provides total engine protection and can be used in start-stop driving and short distance driving because of its excellent cold start properties.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA C2	HONDA -	MITSUBISHI .
API SN	ILSAC GF-5	SUBARU .
FIAT 9.55535-DS1	JAGUAR-LAND ROVER ST-	SUZUKI.
FIAT 9.55535-GS1	JLR.03.5007	TOYOTA .
FORD WSS-M2C950-A	JEEP .	

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,847	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	45,6	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	9,4	
Viscosity Index	ASTM D2270		196	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,8	
Pour point	ASTM D6892	°C	-48	
Flash point	ASTM D92	°C	210	
Sulphated ash content	ASTM D874	%	0,79	



Product information

People buy this product because they need an OW30 engine oil with EURO 6 requirements

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

