

# PYRUS EMS C2 LL-12

## SAE 0W/30

MID SAPS ENGINE OIL C2

**DYADE**  
LUBRICANTS

320105501



### MID SAPS ENGINE OIL C2

This is a full synthetic engine oil that is very suitable for vehicles that need to meet the BMW ll-12 FE specification. This product can be used in vehicles that require an ACEA C2 specification. This product is mandatory in the newest BMW gasoline and diesel engines. It provides excellent fuel economy results and can be used in start-stop driving as well as long distance driving.

### FUEL ECONOMY RATING



### SPECIFICATIONS

ACEA C2	HYUNDAI .	MB 229.61
ALFA ROMEO -	ILSAC GF-5	MINI -
API SN PLUS	JAGUAR-LAND ROVER ST-	MITSUBISHI .
API SP	JLR.03.5007	OPEL OV 040 1547 - G30
BMW LONGLIFE-I2 FE	JEEP .	ROLLS-ROYCE -
FIAT 9.55535-DS1	KIA .	SSANG YONG -
FIAT 9.55535-GS1	LANCIA .	SUBARU .
FORD WSS-M2C950-A	LEXUS -	SUZUKI .
GENESIS -	MASERATI -	TOYOTA .
HONDA -	MB 227.61	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,841
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	54
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	9,8
Viscosity Index	ASTM D2270		169
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-57
Flash point	ASTM D92	°C	225
Sulphated ash content	ASTM D874	%	0,8

## Product information

People buy this product because they need an engine oil with the BMW LL-12 FE specification

### CATEGORY

- Passenger Car
- Engine Oil

### BASE OIL

- Full Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

