

E-HYBRID C5 MB 229.71

SAE 0W/20

FULL SYNTHETIC ENGINE OIL FOR HYBRID VEHICLES

DYADE
LUBRICANTS

320106401



FULL SYNTHETIC ENGINE OIL FOR HYBRID VEHICLES

In addition to regular combustion engines, this is a full synthetic engine oil specifically designed for hybrid vehicles. In hybrid vehicles the combustion engines (ICE) are smaller, and as switching between the combustion engine and electrical engine increases friction tremendously, different engine oils are needed. This product has excellent speed bearing protection, excellent sludge control and compatibility with polymeric materials which are used in hybrid engines. The MB 229.71 specification means that this product is also capable of serving some of the latest Mercedes-Benz E-Class engines, including the 2017 E 220 d 4MATIC All-Terrain 213.217 and the 2017 E 220 d 4MATIC Coupé 238.315.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA C5	FORD WSS-M2C945-A	LEXUS -
ACEA C6	FORD WSS-M2C945-B1	LINCOLN -
ACURA -	FORD WSS-M2C946-A	MAZDA -
API SN PLUS	FORD WSS-M2C946-B1	MB 229.71
API SN / RC	FORD WSS-M2C947-A	MB 229.72
API SP	FORD WSS-M2C947-B1	MG -
API SP / RC	FORD WSS-M2C962-A1	MINI -
ASTON MARTIN .	GM DEXOS™	NISSAN .
BMW LONGLIFE-14FE+	GMC -	OPEL OV 040 1547 - A20
BMW LONGLIFE-17FE+	HONDA -	PERODUA -
BUICK -	HYUNDAI .	ROEWE -
CADILLAC -	ILSAC GF-5	SCION -
CHEVROLET -	ILSAC GF-6 A	SUBARU .
CHRYSLER MS 12145	INFINITI -	SUZUKI .
CHRYSLER MS 6395	JAGUAR-LAND ROVER ST-	TATA -
DODGE -	JLR.03.5006	TIANJIN -
FIAT 9.55535-CR1	JAGUAR-LAND ROVER ST-	TOYOTA .
FIAT 9.55535-DM1	JLR.51.5122	VOLVO VCC RBS0-2AE
FIAT 9.55535-DSX	JEEP .	
FIAT 9.55535-GSX	KIA .	

Product information

People buy this product because they need a lubricant for their (HYBRID) vehicle with MB 229.71 specs.

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L



E-HYBRID C5 MB 229.71

SAE 0W/20

FULL SYNTHETIC ENGINE OIL FOR HYBRID VEHICLES

DYADE
LUBRICANTS

320106401

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,842
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	39,3
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	8,3
Viscosity Index	ASTM D2270		192
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,8
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	0,79

Product information

People buy this product because they need a lubricant for their (HYBRID) vehicle with MB 229.71 specs.

CATEGORY

- Passenger Car
- Engine Oil

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

