

# SALIX SP SAE 0W/40

FULL SYNTHETIC ENGINE OIL SP

**DYADE**  
LUBRICANTS

320107101



## FULL SYNTHETIC ENGINE OIL SP

Dyade Lubricants introduces its advanced synthetic engine oil, compliant with the contemporary API SP standards. With its SAE 0W-40 viscosity grade, engines achieve peak fuel efficiency. Our formulation ensures superior protection against wear and maintains pristine engine conditions. Tailored for the latest turbocharged gasoline and diesel cars and light-duty vehicles, it's adeptly crafted for modern Turbocharged Gasoline Direct Injection (TGD) engines, addressing LSPI (Low Speed Pre Ignition) challenges. Benefit from smooth cold starts due to its remarkable low-temperature fluidity, enjoy reduced fuel consumption and CO2 emissions, and trust in its comprehensive engine protection for both cleanliness and longevity.

## FUEL ECONOMY RATING



## SPECIFICATIONS

ACEA A3 / B4	PORSCHE A40	VW 505.00
API SP	RENAULT RN 0700	
BMW LONGLIFE-01	RENAULT RN 0710	
MB 229.5	VW 502.00	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0.845
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	61,9
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	12,7
Viscosity Index	ASTM D2270		210
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	12,5
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	222
Sulphated ash content	ASTM D874	%	

## Product information

People buy this product because Dyade Lubricants guarantees peak fuel efficiency, superior engine protection, and optimal performance for modern turbocharged vehicles.

### CATEGORY

- Passenger Car
- Engine Oil

### BASE OIL

- Full Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

