MANDRA GAS SAE 5W/30 LPG, CNG AND DUAL FUEL POWERED GAS ENGINE OIL



FUEL ECONOMY RATING

320107301

LPG, CNG AND DUAL FUEL POWERED GAS ENGINE OIL

Dyade Lubricants introduces a superior synthetic lubricant, crafted from elite base oils and the most advanced additives available. Tailored specifically for LPG, CNG, and Dual Fuel passenger vehicles, it addresses the heightened combustion temperatures of gas engines, employing innovative technology to shield valves and counteract acid formations. Ideal for passenger car gas engines fueled by LPG, CNG, and Dual Fuel, its premium composition supports prolonged drain intervals in line with manufacturer recommendations. With Dyade, users can expect exceptional engine protection, ensuring cleanliness and longevity, smooth cold starts due to its unparalleled low-temperature fluidity, and extended oil drain periods.

COLCICICATIONS

SPECIFICATIONS				
ACEA C3	MB 229.51			
API SN / CF	VW 502.00.00			
GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,852	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	68,1	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	11,7	
Viscosity Index	ASTM D2270		168	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,1	
Pour point	ASTM D6892	٦°	-42	
Flash point	ASTM D92	٦°	220	
Sulphated ash content	ASTM D874	%		



Product information

LUBRICANTS

People buy this product because Dyade Lubricants delivers advanced protection for gas engines, ensuring longevity, optimal cold starts, and extended maintenance intervals.

CATEGORY



BASE OIL Full Synthetic

AVAILABLE PACKAGING





All data on this technical data sheet is indicative only

202401V01

MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

TYPOGRAAF 16 | 6921 VB DUIVEN

#