

LUBRICANTS

320200101



HEAVY DUTY ENGINE OIL

This is a high quality mineral heavy duty truck engine oil suitable for naturally aspirated or supercharged diesel and gasoline engines. This product is recommended for fixed diesel engines, and mixed fleets of trucks and cars. The additive technology used in these products ensure long and reliable protection of all the engine parts. These products meet a variety of OEM specifications.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA E2 / E1	MB 227	ZF TE-ML 03B
API CF-4 / SG	MB 228	ZF TE-ML 05K
CATERPILLAR TO-2	MIL MIL-L-2104 E	
MAN 270	MIL MIL-L-46152 E	

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,875	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	41	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	6,7	
Viscosity Index	ASTM D2270		118	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6	
Pour point	ASTM D6892	°C	-24	
Flash point	ASTM D92	°C	212	
Sulphated ash content	ASTM D874	%	0,7	

Product information

People buy this product because they need an HDO SAE 10W Engine Oil.

CATEGORY

- Heavy Duty
- Engine Oil

BASE OIL

Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

