





HEAVY DUTY ENGINE OIL

This is a high quality mineral heavy duty truck engine oil suitable for naturally aspirated or supercharged diesel and gasoline engines. This product is recommended for fixed diesel engines, and mixed fleets of trucks and cars. The additive technology used in these products ensure long and reliable protection of all the engine parts. These products meet a variety of OEM specifications.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA E2 / E1	MB 227	ZF TE-ML 03A
API CF-4 / SG	MB 228	ZF TE-ML 06A
CATERPILLAR TO-2	MIL MIL-L-2104 E	ZF TE-ML 07D
MAN 270	MIL MIL-L-46152 E	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,88
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	54
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	7,6
Viscosity Index	ASTM D2270		103
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6
Pour point	ASTM D6892	°C	-22
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	0,7



Product information

People buy this product because they need an HDO SAE 20W Engine Oil.

CATEGORY

- Heavy Duty
- Engine Oil

BASE OIL

Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

