

BUXUS CH-4/SJ SAE 15W/40

HEAVY DUTY ENGINE OIL

DYADE
LUBRICANTS

320201101



HEAVY DUTY ENGINE OIL

This is a high-quality diesel engine oil that meets a variety of American and European specifications. This product can be used in EURO II, EURO III and some EURO IV engines (not with DPF filter). This product is perfectly suitable for the whole heavy-duty portfolio like modern diesel trucks, off-road equipment and other heavy material. Also this product is very suitable for passenger car diesels, vans and light trucks. The product has been formulated in order to extend the drain interval of the lubricant and has excellent anti-corrosion properties.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA A3 / B4	CUMMINS CES 20077	MACK EO-N
ACEA E7	CUMMINS CES 20078	MAN M3275-1
ALLISON C4	DAIMLER TRUCK DTRF 15B110	MB 228.3
API CF-4	DETROIT DIESEL DFS 93K215	MB 229.1
API CG-4	DEUTZ DQC-III-10	MTU OIL CATEGORY 1
API CH-4	DEUTZ DQC-III-18	MTU OIL CATEGORY 2
API CI-4 / SL	GLOBAL DHD-1	RENAULT RLD
CATERPILLAR ECF-1A	IVECO 18-1804 CLASSE T2 E7	RENAULT RLD-2
CATERPILLAR ECF-2	JASO DH-1	VOLVO VDS-3
CATERPILLAR TO-2	MACK EO-L	
CUMMINS CES 20076	MACK EO-M PLUS	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,89
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	98
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,8
Viscosity Index	ASTM D2270		142
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,5
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	221
Sulphated ash content	ASTM D874	%	1,59

Product information

People buy this product because they need a CH-4/SJ HD oil.

CATEGORY

- Heavy Duty
- Engine Oil

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

