

HEAVY DUTY ENGINE OIL





## **HEAVY DUTY ENGINE OIL**

This product is a high-performance diesel engine oil that is developed according to one of the latest emission regulations. This product is suitable for heavily loaded diesel engines. The product can be used in modern diesel engines of trucks, buses, off-road equipment and other heavy-duty materials. This product is highly recommended for diesel engines that meet EURO I, EURO II, EURO III, EURO IV and EURO V emission requirements. It can be used in vehicles with or without DPF filters and is also applicable in vehicles with SCR NOx reduction systems. It is an excellent product that performs well under extreme operating conditions and increases the lifetime of the equipment. This is a perfect product for the complete fleet.

### **FUEL ECONOMY RATING**



### **SPECIFICATIONS**

| ACEA EII           | CUMMINS CES 20086         | MACK EO-S 4.5        |  |
|--------------------|---------------------------|----------------------|--|
| ACEA E9-16         | DAF PSQL 2.1 E            | MAN M3575            |  |
| ALLISON C4         | DAIMLER TRUCK DTFR 15C100 | MAN M3775            |  |
| API CI-4           | DETROIT DIESEL DFS 93K215 | MB 228.31            |  |
| API CI-4 PLUS      | DETROIT DIESEL DFS 93K218 | MTU OIL CATEGORY 2.1 |  |
| API CJ-4           | DETROIT DIESEL DFS 93K222 | RENAULT RGD          |  |
| API CK-4           | DEUTZ DQC-III-10 LA       | RENAULT RLD          |  |
| API SN             | DEUTZ DQC-III-18 LA       | RENAULT RLD-2        |  |
| CATERPILLAR ECF-1A | FORD WSS-M2C171-F1        | RENAULT RLD-3        |  |
| CATERPILLAR ECF-2  | JASO DH-1                 | RENAULT RLD-4        |  |
| CATERPILLAR ECF-3  | JASO DH-2                 | RENAULT RXD          |  |
| CATERPILLAR TO-2   | JD JDQ-78X                | VOLVO VDS-3          |  |
| CUMMINS CES 20076  | MACK EO-M PLUS            | VOLVO VDS-4          |  |
| CUMMINS CES 20077  | MACK EO-N                 | VOLVO VDS-4.5        |  |
| CUMMINS CES 20078  | MACK EO-N PREMIUM PLUS    |                      |  |
| CUMMINS CES 20081  | MACK EO-O PREMIUM PLUS    |                      |  |

| GRADE                        | METHOD     | UNIT     | VALUE |    |
|------------------------------|------------|----------|-------|----|
| Density                      | ASTM D4052 | kg/l     | 0,862 |    |
| Kinematic viscosity @ 40 °C  | ASTM D445  | mm²/s    | 75,1  |    |
| Kinematic viscosity @ 100 °C | ASTM D445  | mm²/s    | 11,4  |    |
| Viscosity Index              | ASTM D2270 |          | 144   |    |
| B.N. (HCL04 method)          | ASTM D2896 | mg KOH/g | 11,1  |    |
| Pour point                   | ASTM D6892 | °C       | -36   |    |
| Flash point                  | ASTM D92   | °C       | 216   | _  |
| Sulphated ash content        | ASTM D874  | %        | 1,43  | 13 |
|                              |            | -        | DYADÉ |    |

All data on this technical data sheet is indicative only

202401V01



# **Product information**

People buy this product because they need an E7 CI-4 HD engine oil

### **CATEGORY**

- Heavy Duty
- Engine Oil

## BASE OIL

Mineral

## **AVAILABLE PACKAGING**

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L