

RUMEX CK-4 SAE 10W/30

SEMI-SYNTHETIC HEAVY DUTY ENGINE OIL

DYADE
LUBRICANTS

320202801



SEMI-SYNTHETIC HEAVY DUTY ENGINE OIL

This is a semi-synthetic heavy duty engine oil of the latest generation. This product meets a variety of specifications and is specifically developed in order to have total engine protection at extreme long interval ranges. This product has a high shear resistance and operates very well in a very broad operating temperature range. This product can be used in off-road and on-road heavy duty applications. It can be used in vehicles with and without turbocharges or after treatment devices. Very high levels of fuel economy are met with this product. This product is compatible with emission control technology EURO IV, EURO V, and VI.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA E11	CUMMINS CES 20086	MACK EO-S 4.5
ACEA E9-16	DAF PSQL 2.1 E	MAN M3575
ALLISON C4	DAIMLER TRUCK DTFR 15C100	MAN M3775
API CI-4	DETROIT DIESEL DFS 93K215	MB 228.31
API CI-4 PLUS	DETROIT DIESEL DFS 93K218	MTU OIL CATEGORY 2.1
API CJ-4	DETROIT DIESEL DFS 93K222	RENAULT RGD
API CK-4	DEUTZ DQC-III-10 LA	RENAULT RLD
API SN	DEUTZ DQC-III-18 LA	RENAULT RLD-2
CATERPILLAR ECF-1A	FORD WSS-M2C171-F1	RENAULT RLD-3
CATERPILLAR ECF-2	JASO DH-1	RENAULT RLD-4
CATERPILLAR ECF-3	JASO DH-2	RENAULT RXD
CATERPILLAR TO-2	JD JDQ-78X	VOLVO VDS-3
CUMMINS CES 20076	MACK EO-M PLUS	VOLVO VDS-4
CUMMINS CES 20077	MACK EO-N	VOLVO VDS-4.5
CUMMINS CES 20078	MACK EO-N PREMIUM PLUS	
CUMMINS CES 20081	MACK EO-O PREMIUM PLUS	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,858
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	74,1
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	11,6
Viscosity Index	ASTM D2270		151
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9,5
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	232
Sulphated ash content	ASTM D874	%	1

All data on this technical data sheet is indicative only

202401V01



Product information

People buy this product because they need the newest CK-4 HD engine oil

CATEGORY

- Heavy Duty
- Engine Oil

BASE OIL

- Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM