

# RUMEX CK-4 SAE 10W/40

SEMI-SYNTHETIC HEAVY DUTY ENGINE OIL

**DYADE**  
LUBRICANTS

320202901



## SEMI-SYNTHETIC HEAVY DUTY ENGINE OIL

This is a semi-synthetic heavy duty engine oil of the latest generation. This product meets a variety of specifications and is specifically developed in order to have total engine protection at extreme long interval ranges. This product has a high shear resistance and operates very well in a very broad operating temperature range. This product can be used in off-road and on-road heavy duty applications. It can be used in vehicles with and without turbocharges or after treatment devices. Very high levels of fuel economy are met with this product. This product is compatible with emission control technology EURO IV, EURO V, and VI.

## FUEL ECONOMY RATING



## SPECIFICATIONS

ACEA E11	CUMMINS CES 20086	MAN M3575
ACEA E9-16	DAIMLER TRUCK DTFR 15C100	MAN M3775
ALLISON C4	DETROIT DIESEL DFS 93K215	MB 228.31
API CI-4	DETROIT DIESEL DFS 93K218	MTU OIL CATEGORY 2.1
API CI-4 PLUS	DETROIT DIESEL DFS 93K222	RENAULT RGD
API CJ-4	DEUTZ DQC-III-10 LA	RENAULT RLD
API CK-4	DEUTZ DQC-III-18 LA	RENAULT RLD-2
API SN	FORD WSS-M2C171-F1	RENAULT RLD-3
CATERPILLAR ECF-1A	JASO DH-1	RENAULT RLD-4
CATERPILLAR ECF-2	JASO DH-2	RENAULT RXD
CATERPILLAR ECF-3	JD JDQ-78X	VOITH RETARDER OIL CLASS B
CATERPILLAR TO-2	MACK EO-M PLUS	VOLVO VDS-3
CUMMINS CES 20076	MACK EO-N	VOLVO VDS-4
CUMMINS CES 20077	MACK EO-N PREMIUM PLUS	VOLVO VDS-4.5
CUMMINS CES 20078	MACK EO-O PREMIUM PLUS	
CUMMINS CES 20081	MACK EO-S 4.5	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,859
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	87,5
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	13,8
Viscosity Index	ASTM D2270		162
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9,5
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	224
Sulphated ash content	ASTM D874	%	1

## Product information

People buy this product because they need the newest CK-4 HD engine oil

### CATEGORY

- Heavy Duty
- Engine Oil

### BASE OIL


- Semi-Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADE-LUBRICANTS.COM  
WWW.DYADEGLOBAL.COM