

YUCCA ELS SAE 10W/40

FULL SYNTHETIC HEAVY DUTY ENGINE OIL

DYADE
LUBRICANTS

320203201



FULL SYNTHETIC HEAVY DUTY ENGINE OIL

This is a full synthetic heavy duty engine oil that meets the highest performance standards for the newest large truck fleets. This product is recommended for EURO V and EURO VI engines. This product enables very high levels of fuel economy and protects the engine all year round for very long interval ranges. This product can be used in vehicles that are equipped with after treatment devices (EGR, SCR, DPF etc.). This is one of the best products in the market for maintaining the newer truck portfolio.

FUEL ECONOMY RATING



SPECIFICATIONS

ACEA E11	CUMMINS CES 20086	MACK EO-S 4.5
ACEA E4	DAF EXTENDED DRAIN	MAN M3271-1
ACEA E6-16	DAIMLER TRUCK DTFR I3D110	MAN M3477
ACEA E7	DAIMLER TRUCK DTFR 15C100	MAN M3575
ACEA E8	DAIMLER TRUCK DTFR 15C110	MAN M3775
ACEA E9-16	DAIMLER TRUCK DTFR 15C120	MB 228.31
API CI-4	DETROIT DIESEL DFS 93K215	MB 228.51
API CI-4 PLUS	DETROIT DIESEL DFS 93K218	MB 228.52
API CJ-4	DETROIT DIESEL DFS 93K222	MB 235.28
API CK-4	DEUTZ DQC IV-10 LA	MTU OIL CATEGORY 2.1
API SN	DEUTZ DQC-IV-18 LA	MTU OIL CATEGORY 3.1
JASO DH-1	DEUTZ TTCD	RENAULT RGD
JASO DH-2-17	FORD WSS-M2C171-F1	RENAULT RLD
ALLISON C4	IVECO 18-1804 CLASSE T2 E7	RENAULT RLD-2
CASE MAT 3571	IVECO 18-1804 CLASSE TLS E6	RENAULT RLD-3
CASE MAT 3572	IVECO 18-1804 CLASSE TLS E9	RENAULT RLD-4
CATERPILLAR ECF-1A	IVECO 18-1809 CLASSE NG2	RENAULT RXD
CATERPILLAR ECF-2	JD JDQ-78X	SCANIA LA
CATERPILLAR ECF-3	LIEBHERR LH-00-ENG5C LA	VOITH RETARDER OIL CLASS B
CATERPILLAR TO-2	MACK EO-M PLUS	VOLVO VDS-3
CUMMINS CES 20077	MACK EO-N	VOLVO VDS-4
CUMMINS CES 20078	MACK EO-N PREMIUM PLUS	VOLVO VDS-4.5
CUMMINS CES 20081	MACK EO-O PREMIUM PLUS	

Product information

People buy this product because they need EURO VI truck engine oil

CATEGORY

- Heavy Duty
- Engine Oil

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L



YUCCA ELS SAE 10W/40

FULL SYNTHETIC HEAVY DUTY ENGINE OIL

DYADE
LUBRICANTS

320203201

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,864
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	88,2
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,8
Viscosity Index	ASTM D2270		157
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	12,8
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	226
Sulphated ash content	ASTM D874	%	0,98

Product information

People buy this product because they need
EURO VI truck engine oil

CATEGORY

- Heavy Duty
- Engine Oil

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

