

2-STROKE MOTORCYCLE OIL



320300301



2-STROKE MOTORCYCLE OIL

This is a 2-stroke engine oil that has been made from the most excellent semi-synthetic base oils. Additives are added that ensure complete engine lubrication. It reduces deposits in the combustion chamber and flushing ports. Also, it contains very high cleaning properties in order to clean the spark plugs. This ensures that the engine will keep its power over time. The formulation ensures that there is low to little smoke formation and this product is perfectly suitable for high-speed as well as heavily loaded air-cooled 2-stroke engines. This product can also be used in engines with water cooling/radiator cooling.

FUEL ECONOMY RATING



SPECIFICATIONS

API TC	JASO FC
ISO L-EGD	JASO FD

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,866	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	64,6	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	9,5	
Viscosity Index	ASTM D2270		129	
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	1,4	
Pour point	ASTM D6892	°C	-24	
Flash point	ASTM D92	°C	116	
Sulphated ash content	ASTM D874	%	0,14	

Product information

People buy this product because they need an excellent LOW SMOKE semi-synthetic 2-stroke engine oil

CATEGORY

- 2-Stroke
- Motor Cycle

BASE OIL

Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

