

LUBRICANTS

320300801



2-STROKE SNOWSCOOTER

This is a synthetic lubricant that is specifically designed for the use in snow scooters and snowmobiles. The product is developed to function particularly well in cold temperature climates. We have added our ester technology that ensures a strong lubricating film and an excellent protection at high operating temperatures. It is pre-diluted for easy mixing, has a very low pour point and ensures free flowing of fuel, even at very low temperatures. This is primarily suitable for the latest generation of 2-cycle snowmobiles equipped with fuel injection systems (EFI or DFI) and/or exhaust power valve engines. It is recommended as an injector oil or at a 50:1 ratio in carburetted or direct fuel injection

FUEL ECONOMY RATING



SPECIFICATIONS

API TC	NMMA TC-W3
JASO FC	

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,857	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	42,7	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	7,9	
Viscosity Index	ASTM D2270		158	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	5,1	
Pour point	ASTM D6892	°C	-42	
Flash point	ASTM D92	°C	104	
Sulphated ash content	ASTM D874	%	0	
Sulphateu asii content	ASTI1 D0/4	/0	<u> </u>	

Product information

People buy this product because they need an excellent 2-stroke oil for snowscooters

CATEGORY

- 2-Stroke
- Snow Scooter

BASE OIL

Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

