CALTHA M-4S SAE 15W/50 4-STROKE MOTORCYCLE ENGINE OIL





FUEL ECONOMY RATING

SPECIFICATIONS

320400701

4-STROKE MOTORCYCLE ENGINE OIL

This is an advanced generation of semi-synthetic 4-stroke motorcycle and scooter engine oils. It can be used for both incidental traffic vehicles as well as daily-use vehicles. This product has been based on a formulation that ensures extreme pressure additives in order to maintain the gearbox optimally. It prevents the wet clutches from slipping and the dispersant and detergents that are added ensure optimal cleanliness. This product can be used in city traffic as well as highway traffic and can be used in all types of motorcycles, guads, 4-stroke scooters.

API SL	JASO MA2			
GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,876	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	134	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	17,6	
Viscosity Index	ASTM D2270		145	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7	
Pour point	ASTM D6892	°C	-36	
Flash point	ASTM D92	°C	237	
Sulphated ash content	ASTM D874	%		

MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

Product information


People buy this product because they need an all-round 4-stroke motorcycle engine oil





Semi-Synthetic

AVAILABLE PACKAGING



All data on this technical data sheet is indicative only

202401V01



TYPOGRAAF 16 | 6921 VB DUIVEN

#