

VINCA TGO GL 1&3

SAE 140

UNIVERSAL GEAR OIL GL-1&3

DYADE
LUBRICANTS

320600201



UNIVERSAL GEAR OIL GL-1&3

This is a high quality gear oil that is developed for low charged transmissions. This product can be used in manual gearboxes and rear axles that are in need of an API GL-1 & GL-3 specification. This product is made out of high quality mineral base oils and provides reliable lubrication. Anti-Foam additives are added to the formulation in order to optimize the result of the lubricant.

FUEL ECONOMY RATING



SPECIFICATIONS

API GL-1 VOLVO 97305
API GL-3

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,902
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	389
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	27,3
Viscosity Index	ASTM D2270		96
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-18
Flash point	ASTM D92	°C	230
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because they need a mineral GL-1 / GL-3 Gear Oil

CATEGORY

- Automotive
- Gear Oil

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM