

VINCA TGO GL 1&3

SAE 80W/90

UNIVERSAL GEAR OIL GL-1&3

DYADE
LUBRICANTS

320600301



UNIVERSAL GEAR OIL GL-1&3

This is a high quality gear oil that is developed for low charged transmissions. This product can be used in manual gearboxes and rear axles that are in need of an API GL-1 & GL-3 specification. This product is made out of high quality mineral base oils and provides reliable lubrication. Anti-Foam additives are added to the formulation in order to optimize the result of the lubricant.

FUEL ECONOMY RATING



SPECIFICATIONS

API GL-1 VOLVO 97305
API GL-3

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,896
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	142
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,6
Viscosity Index	ASTM D2270		102
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	212
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because they need a mineral GL-1 / GL-3 Gear Oil

CATEGORY

- Automotive
- Gear Oil

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

