

VINCA TGO GL-4

SAE 80W/90

UNIVERSAL GEAR OIL GL-4

DYADE
LUBRICANTS

320600701



UNIVERSAL GEAR OIL GL-4

This is a high quality mineral gear oil that has been specifically developed for extreme pressure circumstances and meets that GL-4 specification. The anti-friction additive packages that are used in this product ensure easy shifting. This product is specifically developed to avoid corrosion of copper alloys and can be used in synchromesh gearboxes, transfer boxes, mechanical steering controls and most rear axles. The Anti-wear properties of this products ensure long transmission life.

FUEL ECONOMY RATING



SPECIFICATIONS

API GL-4 MIL MIL-L-2105

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,892
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	148
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,7
Viscosity Index	ASTM D2270		98
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-30
Flash point	ASTM D92	°C	224
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because they need an extreme pressure GL-4 manual gear oil

CATEGORY

- Automotive
- Gear Oil

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

