

VINCA TGO GL-4

SAE 85W/90

UNIVERSAL GEAR OIL GL-4

DYADE
LUBRICANTS

320600801



UNIVERSAL GEAR OIL GL-4

This is a high quality mineral gear oil that has been specifically developed for extreme pressure circumstances and meets that GL-4 specification. The anti-friction additive packages that are used in this product ensure easy shifting. This product is specifically developed to avoid corrosion of copper alloys and can be used in synchromesh gearboxes, transfer boxes, mechanical steering controls and most rear axles. The Anti-wear properties of this products ensure long transmission life.

FUEL ECONOMY RATING



SPECIFICATIONS

API GL-5
MIL L-2105 C

MIL L-2105 D

| GRADE | METHOD | UNIT | VALUE |
|------------------------------|------------|--------------------|-------|
| Density | ASTM D4052 | kg/l | 0,896 |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm ² /s | 155 |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm ² /s | 14,9 |
| Viscosity Index | ASTM D2270 | | 95 |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | |
| Pour point | ASTM D6892 | °C | -21 |
| Flash point | ASTM D92 | °C | 210 |
| Sulphated ash content | ASTM D874 | % | |

Product information

People buy this product because they need an extreme pressure GL-4 manual gear oil

CATEGORY

- Automotive
- Gear Oil

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM