

VINCA MGO GL-5 UNI

SAE 75W/90

UNIVERSAL GEAR OIL GL-5

DYADE
LUBRICANTS

320601301



UNIVERSAL GEAR OIL GL-5

This is a full synthetic GL-5 manual transmission gear oil that is known for its wide universal use. This product can be used in all gearboxes, transfer boxes and differentials of trucks and 4-wheel drives. This manual gear oil is suitable for synchronized gearboxes as well as heavily loaded differentials. This gear oil performs very well in severe conditions. This product contains effective anti-scuffing additives and can be used for hypoid gears that have significant displacement of axes. This product operates under various combinations of high-speed/shock load and lowspeed/high-torque conditions.

FUEL ECONOMY RATING



SPECIFICATIONS

API GL-4	MAN 341 Z-2	ZF TE-ML 07A
API GL-5	MAN 342 M-3	ZF TE-ML 08
API MT-1	MB 235.11	ZF TE-ML 12B
ARVIN MERITOR 0-76-N	MB 235.8	ZF TE-ML 12L
BMW OSP	MIL PRF-2105E	ZF TE-ML 12N
CHRYSLER MS 9763	RENAULT B0032 / 3 ANNEX 3	ZF TE-ML 16F
DAF GL5 / MIL-PRF-2105E	SAE J 2360	ZF TE-ML 17B
IVECO MIL-PRF-2105E	SCANIA STO 1:0	ZF TE-ML 19C
MACK GO-J	VOLVO 97312	ZF TE-ML 21B
MAN 341 E-3	ZF TE-ML 02B	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,868
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	76,3
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	15,2
Viscosity Index	ASTM D2270		203
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because they need a universal full synthetic GL-5 Gear Oil

CATEGORY

- Automotive
- Gear Oil

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

