

# VINCA MGO GL-5 LS

## SAE 75W/90

UNIVERSAL LIMITED SLIP GEAR OIL GL-5

**DYADE**  
LUBRICANTS

320602101



### FUEL ECONOMY RATING



### UNIVERSAL LIMITED SLIP GEAR OIL GL-5

This is a semi-synthetic GL-5 limited slip gear oil that is used in differentials with a limited slip or lock-up mechanism, requiring a low viscosity gear oil. This product contains additive packages that ensure that friction properties are adapted to limited slip applications. It ensures easy shifting, long transmission life and provides excellent protection against oxidation and corrosion. This product can be used in hypoid rear axles and transfer boxes of high power vehicles, SUV's and ALL-WHEEL Drives. This product can also be used for 75W85 applications. This gear oil performs very well in severe conditions. This product contains effective anti-scuffing additives and can be used for hypoid gears that have significant displacement of axes. This product operates under various combinations of high-speed/shock load and lowspeed/high-torque conditions.

### SPECIFICATIONS

API GL-5  
MIL MIL-L-2105 D  
MIL MIL-L-2105 C

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,873
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	86,1
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	14,4
Viscosity Index	ASTM D2270		174
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	185
Sulphated ash content	ASTM D874	%	

## Product information

People buy this product because they need a low viscosity Limited Slip GL-5 Gear Oil

### CATEGORY

- Automotive
- Gear Oil

### BASE OIL

- Semi-Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

