VINCA LGO GL-5 SAE 75W/90 SS

UNIVERSAL SEMI-SYNTHETIC GEAR OIL



FUEL ECONOMY RATING

SPECIFICATIONS

API GL-5

MIL MIL-L-2105 D

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,881
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	81
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	15
Viscosity Index	ASTM D2270		196
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	٦°	-45
Flash point	ASTM D92	٦°	206
Sulphated ash content	ASTM D874	%	

320602601

UNIVERSAL SEMI-SYNTHETIC GEAR OIL

This is a semi-synthetic GL-5 manual gear oil that is developed for applications where gear shifting problems occur because thicker oils have been used. This product helps to reduce oil degradation and extends the service life. This gear oil is developed with a high viscosity index that ensures excellent fluidity at low temperatures as well. An excellent product to reduce the current gear shifting problems and extend the lifetime of the vehicle.



```<u>'</u>''''

People buy this product because they need a GL-5 Gear Oil that solves gear-shifting problems because of thicker oil usage

LUBRICANTS

CATEGORY

📕 Automotive

📕 Gear Oil

BASE OIL

Semi-Synthetic

AVAILABLE PACKAGING





All data on this technical data sheet is indicative only

202401V01

MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V. TYPOGRAAF 16 | 6921 VB DUIVEN THE NETHERLANDS

#