

# VINCA LGO GO

## SAE 75W/80

UNIVERSAL GEAR OIL

**DYADE**  
LUBRICANTS

320602701



### UNIVERSAL GEAR OIL

This is a GL-4 + manual gear oil that can be used for almost all manual gearboxes of passenger car vehicles. This product has been developed in order to reduce the gearbox oil product assortment. This product has been tested on a variety of properties. The result is that it meets the general performance requirements of a very wide portfolio of OEM brands and models. This product can be used all-year round and in all kinds of weather conditions. It ensures smooth shifting and extends transmissions lifetime.

### FUEL ECONOMY RATING



### SPECIFICATIONS

API GL-4 +	HYUNDAI 02200-00130 TOD	TOYOTA JWS 227
BMW 83220309031	LAND ROVER TYK500030	VOLVO 97308
BMW MTF LT-2	MB 235.1	VOLVO 97309
FIAT 9.55550-MX3	MITSUBISHI MZ312644	VOLVO 97310
FIAT 9.55550-MZI	NISSAN 999MP-MTF20P	VW G 052 171
FORD ESD-M2C186-A	NISSAN MT-XZ	VW G 052 527
FORD WSS-M2C200-D2	PSA 9730 A2	VW G 052 726
GM 1940182	PSA 9730 A8	VW G 055 538
GM 1940768	PSA B71 2330	
HONDA MTF 94	SUBARU K0321-F0090	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,871
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	45,8
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	9,1
Viscosity Index	ASTM D2270		185
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	205
Sulphated ash content	ASTM D874	%	

## Product information

People buy this product because they need a universal GL 4+ manual gear oil for the whole fleet

### CATEGORY

- Automotive
- Gear Oil

### BASE OIL

- Mineral

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

