

VITIS ATF UNI III-G

UNIVERSAL ATF DEXRON III-G

DYADE
LUBRICANTS

320700201



UNIVERSAL ATF DEXRON III-G

This is a semi-synthetic automatic transmission oil. This product can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements. This product had a very high viscosity index and is formulated in order to extend the oil lifetime. It ensures excellent low temperature pumpability and extends the transmission lifetime.

FUEL ECONOMY RATING



SPECIFICATIONS

ALLISON C4	MB 236.8	ZF TE-ML 04D
FORD MERCON	MB 236.9	ZF TE-ML 05L
GM 6417-M DEXRON III-G	VOITH H55.6335XX	ZF TE-ML 09
GM DEXRON II-D	VOLVO STD 1273.25 (97325)	ZF TE-ML 11B
GM DEXRON III-H	VOLVO STD 1273.35 (97335)	ZF TE-ML 14A
MAN 339 VI / Z1	VOLVO STD 1273.37 (97337)	ZF TE-ML 17C
MB 236.5	VOLVO STD 1273.40 (97340)	ZF TE-ML 21L
MB 236.6	VOLVO STD 1273.41 (97341)	
MB 236.7	ZF TE-ML 03D	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	33,9
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,1
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	196
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because they need an ATF with Dexron III-G specification

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

- Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM