

VITIS ATF UNI III-H WHITE

UNIVERSAL ATF DEXRON III-H

DYADE
LUBRICANTS

320700401



UNIVERSAL ATF DEXRON III-H

This ATF III-H is a high-quality Automatic Transmission Fluid that is developed from the most solvent base oils. This product can be used in automatic gearboxes that require Dexron III-H lubricants. It is also suitable for power steering systems. This ATF III-H has a very high viscosity index and offers resistance against corrosion and foam building. It also has good anti-oxidation and anti-wear properties. The low pour point of this ATF III-H ensures that a good protection is offered also at low temperatures and cold starts.

FUEL ECONOMY RATING



SPECIFICATIONS

ALLISON C4	MB 236.6	ZF TE-ML 03D
DAIMLER TRUCK DTFR 13C140	MB 236.7	ZF TE-ML 04D
DAIMLER TRUCK DTFR 13C150	MB 236.8	ZF TE-ML 05L
DAIMLER TRUCK DTFR 13C170	MB 236.9	ZF TE-ML 09
FORD MERCON	VOITH H55.6335XX	ZF TE-ML 11B
GM 6417-M DEXRON III-G	VOLVO STD 1273.25 (97325)	ZF TE-ML 14A
GM DEXRON II-D	VOLVO STD 1273.35 (97335)	ZF TE-ML 17C
GM DEXRON III-H	VOLVO STD 1273.37 (97337)	ZF TE-ML 21L
MAN 339 VI/ZI	VOLVO STD 1273.40 (97340)	
MB 236.5	VOLVO STD 1273.41 (97341)	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,847
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	33,9
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,1
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	196
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because they need an ATF with Dexron III-H specification

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

- Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

