

VITIS ATF UNI IV

UNIVERSAL ATF DEXRON IV

DYADE
LUBRICANTS

320700501



UNIVERSAL ATF DEXRON IV

This is a full synthetic automatic transmission fluid for universal applications. This product has a wide range of specifications and can be used in vehicles of a wide range of OEM. This product can be used in the latest generation of automatic transmissions and torque converters for most passenger cars, small vans and small buses. This product is formulated in order to ensure smooth gear shifting.

FUEL ECONOMY RATING



SPECIFICATIONS

| | | |
|-----------------------|---------------------|----------------------|
| AISIN-WARNER AW-1 | FIAT 9.55550-AV5 | LAND ROVER LR023288 |
| AISIN-WARNER AW-2 | FORD MERCON LV | MAZDA FZ |
| AISIN-WARNER JWS 3324 | FORD MERCON SP | MB 236.12 |
| ALLISON C4 | FORD WSS-M2C195-A | MB 236.41 |
| BMW 83222152426 | FORD WSS-M2C924-A | MINI M207 |
| BMW 83222167718 | FORD WSS-M2C938-A | NISSAN MATIC-S |
| BMW 83 22 0 397 114 | GM DEXRON HP | TESLA ATF9 / EDF2 |
| BMW 83 22 2 305 397 | GM DEXRON VI | TOYOTA AUTO FLUID WS |
| BMW 83 22 9 407 858 | HONDA DW-1 | VW G 055 005 |
| BMW ATF 3 | HYUNDAI NWS-9638 T5 | VW G 055 162 |
| BMW L I2108 | HYUNDAI SP-IV | VW G 055 540 |
| BMW M-1375.4 | HYUNDAI SPH-IV | VW G 060 162 |
| CHRYSLER 68157995AA | ISUZU WSI | |
| FIAT 9.55550-AV2 | JAGUAR 02JDE26444 | |

| GRADE | METHOD | UNIT | VALUE |
|------------------------------|------------|--------------------|-------|
| Density | ASTM D4052 | kg/l | 0,852 |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm ² /s | 29,4 |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm ² /s | 6,1 |
| Viscosity Index | ASTM D2270 | | 162 |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | |
| Pour point | ASTM D6892 | °C | -45 |
| Flash point | ASTM D92 | °C | 210 |
| Sulphated ash content | ASTM D874 | % | |

Product information

People buy this product because they need an excellent IV ATF

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM