

VITIS ATF UNI X

UNIVERSAL ATF

DYADE
LUBRICANTS

320700801



UNIVERSAL ATF

This ATF is a synthetic transmission oil with extra added friction modifiers in order to gain excellent properties. This ATF can be used for automatic transmissions that are used in several Northern American, European and Asian cars. It meets several OEM specifications like the Ford Mercon V and the Mercedes Benz 236.6. It has a very high viscosity index. Because of its low pour-point it is perfectly suitable for cold starts and operates well in cold climates. It has excellent oxidation stability, anti-wear, anti-corrosion and anti-foaming properties.

FUEL ECONOMY RATING



SPECIFICATIONS

AISIN-WARNER JWS 3309	FIAT 9.55550-AV4	NISSAN MATIC-K
AISIN-WARNER JWS 3314	FORD MERCON V	NISSAN MATIC-W
AISIN-WARNER JWS 3317	FORD WSS-M2C922-A1	PSA P / N Z 000169756
ALLISON TES 295	GM DEXRON III-H	TOYOTA TYPE T-IV
ALLISON TES 389	HONDA ATF Z-1	VW G 052 055
BMW ETL 7045E	HYUNDAI SP-III	VW G 052 162
BMW ETL 8072B	MB 236.11	VW G 052 533
BMW LA 2634	MB 236.3	VW G 052 990
BMW LT 71141	MB 236.7	VW G 055 025
CHRYSLER ATF +3 AND +4	MB 236.1	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,849
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	33,1
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,1
Viscosity Index	ASTM D2270		185
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-54
Flash point	ASTM D92	°C	200
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because it is a multi-use ATF for the whole fleet

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

