

# VITIS ATF MB 7S 236.15

ATF 7 SPEED MB 236.15

**DYADE**  
LUBRICANTS

320701101



### ATF 7 SPEED MB 236.15

This ATF is a fully synthetic Automatic Transmission Fluid specially developed and mandatory for Mercedes Benz 7-speed NAG2FE+ automatic transmissions requiring low viscosity ATF from June 2010. This ATF offers excellent resistance against oxidation, corrosion and foam formation, resulting in a constant high performance during its lifetime. NOTE: NOT backwards compatible with previous MB specs; also not for MB 236.10, MB236.12 and MB 236.14.

### FUEL ECONOMY RATING



### SPECIFICATIONS

MB 236.15

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,843
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	17,3
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	4,4
Viscosity Index	ASTM D2270		172
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-54
Flash point	ASTM D92	°C	178
Sulphated ash content	ASTM D874	%	

## Product information

People buy this product because they need an ATF with specification MB 236.15

### CATEGORY

- Automatic Transmission Fluids
- ATF

### BASE OIL

- Full Synthetic

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

