# **VITIS ATF** MB 9S 236.17

ATF 9 SPEED MB 236.17





## **ATF 9 SPEED MB 236.17**

This is a full synthetic Automatic Transmission Fluid that contains a very low viscosity and high viscosity index. This product has been specifically developed for the Mercedes-Benz 9 speed automatic transmissions. This product ensures significant fuel saving properties and is applicable in automatic transmissions where the MB 236.17 specification is prescribed. This product can be used in the newest 9G-tronic automatic transmissions of the series W9A 700 / NAG3 types. This product is backwards compatible with MB 236.16.

### **FUEL ECONOMY RATING**



## **SPECIFICATIONS**

MB 236.17

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,845	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s		
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	4,8	
Viscosity Index	ASTM D2270		166	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g		
Pour point	ASTM D6892	°C	-54	
Flash point	ASTM D92	°C		
Sulphated ash content	ASTM D874	%		



## **Product information**

People buy this product because they need an ATF with specification MB 236.17

- Automatic Transmission Fluids
- ATF

## BASE OIL

Full Synthetic

## AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

