

VITIS ATF SPC CVT

CONTINUOUS VARIABLE TRANSMISSION FLUID

320701501



FUEL ECONOMY RATING



CONTINUOUS VARIABLE TRANSMISSION FLUID

This is a full synthetic continuous variable transmission fluid that is developed for the modern continue variable transmissions. This product provides protection of metal-to-metal contact points and the belts and pulleys. It has excellent corrosion protection properties and increases the transmission lifetime. This product is specially formulated for the use in CVT boxes that use steel push-belts or chains. Please note that this product is not suitable for Hybrid vehicles.

DYADE
LUBRICANTS

Product information

People buy this product because they need an excellent CVT fluid

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

- Full Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

SPECIFICATIONS

AUDI TL 52180	DEX-CVT	MATIC W
BMW EZL799 / EZL799A	HONDA HCF-2 / HMMF (NO START CLUTCH)	PUNCH EZL799 / EZL799A
DAIHATSU AMIX CVTF DFE	HYUNDAI SP-CVT1	RENAULT ELFMATIC
DAIHATSU AMIX CVTF-DC	JEEP NS-2 / CVTF+4	SUBARU E-CVTF
DODGE NS-2 / CVTF+4	KIA SP-CVT I	SUZUKI CVTF 3320
FORD MERCON C	MAZDA CVTF 3320	TOYOTA CVT FE
FORD WSS-M2C928-A	MB 236.20 / CVT28	TOYOTA TC
FORD WSS-M2C933-A	MINI EZL799 / EZL799A / CVT VI	VOLVO CVT 4959
FUJIIYUUKO I-CVTF FG	MITSUBISHI CVTF J-1	VW G 052 180
GEELY CVTF-EXI	NISSAN NS-1 / NS-2 / NS-3 /	VW G 052 516
GM CVTF GREEN 2 / SATURN		

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,849
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	34,2
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,35
Viscosity Index	ASTM D2270		189
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	
Sulphated ash content	ASTM D874	%	

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM