VITIS ATF SPC 33 FG





ATF SPECIALS FORD

This is a high-quality automatic transmission fluid that is specifically formulated for FORDtransmissions (Glide). This product is formulated in a way that it provides excellent anti-wear and anti-foam properties. Also, it reduces the deposit formation to an absolute minimum which increases the operating lifetime of the transmission. An excellent automatic transmission fluid for FORD automatic transmissions.

FUEL ECONOMY RATING



SPECIFICATIONS

FORD ESP-M2C33-G	FORD SQM2-9007-AA	VOLVO 97330
FORD ESW-M2C33-F	JD JDM J21A	

GRADE	METHOD	UNIT	VALUE	
Density	ASTM D4052	kg/l	0,857	
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	36	
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	7,3	
Viscosity Index	ASTM D2270		173	
B.N. (HCL04 method)	ASTM D2896	mg KOH/g		
Pour point	ASTM D6892	°C	-45	
Flash point	ASTM D92	°C	206	
Sulphated ash content	ASTM D874	%		



Product information

People buy this product because they are in need of an ATF meeting several FORD specifications

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

