

VITIS ATF SPC A/A

ATF SPECIALS A/A

DYADE
LUBRICANTS

320701801



ATF SPECIALS A/A

This is a very in depth formulated automatic transmission fluid that is based on solvent-refined oils. This product can only be used in automatic and semi-automatic gearboxes, power steering where ATF Type A Suffix A oil is prescribed. The high viscosity index and low pour point of this product ensure optimal performance in a very broad temperature range.

FUEL ECONOMY RATING



SPECIFICATIONS

DAIMLER TRUCK DTR 13C120	GM 6032-M DEXRON	MB 236.2
FORD ESP-M2C138-CJ	GM 6137-M DEXRON II-D	
FORD MERCON	GM DEXRON TYPE A. SUFFIX A	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	36,7
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,12
Viscosity Index	ASTM D2270		161
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	1,5
Pour point	ASTM D6892	°C	-42
Flash point	ASTM D92	°C	198
Sulphated ash content	ASTM D874	%	

Product information

People buy this product because they need an ATF Type A Suffix A

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

- Mineral

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

