

VITIS ATF UVL

UNIVERSAL ATF DEXRON ULTRA LOW VISCOSITY

DYADE
LUBRICANTS

320702601



UNIVERSAL ATF DEXRON ULTRA LOW VISCOSITY

The formulation of our transmission fluid provides enhanced anti-wear protection, significantly prolonging transmission lifespan. It ensures smooth gear shifting, offering seamless gear changes with no vibration. Moreover, the product exhibits excellent thermal and oxidation stability, extending oil life and ensuring prolonged performance.

FUEL ECONOMY RATING



SPECIFICATIONS

GM DEXRON ULV FORD WSS-M2C949-A
FORD MERCON ULV

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,847
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	19,8
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	4,55
Viscosity Index	ASTM D2270		151
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	182
Sulphated ash content	ASTM D874	%	

Product information

People use this product because they need a ultra low viscosity ATF

CATEGORY

- Automatic Transmission Fluids
- ATF

BASE OIL

- Semi-Synthetic

AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L