

VISCUM DOT-4 LV

BRAKE FLUID DOT-4 LV

320800301



FUEL ECONOMY RATING



BRAKE FLUID DOT-4 LV

This DOT-4 LV brake fluid is suitable for ABS and ASR brake systems. Its viscosity is lower compared to the original DOT-4 fluid. It is miscible with other DOT-4 and DOT-5.1 products. However, the extremely thin viscosity will be reduced. The risk of vapour lock is strongly reduced due to the product's high 'wet boiling point', which is crucial when asbestos-free brake lining is used or for frequent braking.

PRODUCT SPECIFICATIONS VISCUM DOT-4 LV

GRADE	UNIT	VALUE
Density 20 °C	kg/m ³	1.062
Viscosity -40 °C	cSt	<700
Viscosity 40 °C	cSt	6.4
Wet boiling point	°C	>180
Dry boiling point	°C	>265
Flash point	°C	>110

All data on this technical data sheet is indicative only

201911V02



DYADE

LUBRICANTS

Product information

"People buy this product because they need an excellent DOT-4 LV Brake Fluid."

CATEGORY

Brake Fluids

AVAILABLE GRADE

DOT-4 LV

SPECIFICATIONS

- FMVSS No. 116 DOT 4
- ISO 4925 Class 6
- SAE J 1704
- VW-Norm 50 114
- BMW QV 34001
- Ford WSS-M6C65-A2
- Mercedes MB 331.0
- Toyota
- VW TL 766, Version Z
- GMW 3356

AVAILABLE PACKAGING

- 250 ml
- 500 ml
- 1L
- 20L
- 205L
- 1000L