

BOMBAX STOU SAE 15W/40

STOU AGRICULTURE PERFORMANCE OIL

DYADE
LUBRICANTS

321100401



STOU AGRICULTURE PERFORMANCE OIL

This is a Universal Super Tractor Transmission Oil that is used in engines, transmissions, wet brakes and hydraulic systems of vehicles used in the agriculture/off highway segment. This product has been developed to perform very well also in colder temperature environments. It ensures instant lubrication at usage and reduces risk of wear.

This product can be used for lubricating charged and uncharged diesel engines. It can also be used in 4-stroke gasoline engines and LPG engines. In addition to that it provides excellent properties for the gearbox, differential, final drive, power take-off, wet brakes and hydraulic systems.

Product information

People buy this product because they need an excellent STOU lubricant for Agriculture & off-highway equipment

CATEGORY

■ Agriculture Oils

BASE OIL

■ Mineral

AVAILABLE PACKAGING

■ 12x1 L

■ 5x4 L

■ 4x5 L

■ 20 L

■ 60 L

■ 205 L

■ 1000 L

FUEL ECONOMY RATING

SPECIFICATIONS

| | | |
|------------------------------------|------------------------|--|
| ACEA E3 | EATON VICKERS M-2950-S | NH NH 024C |
| ALLISON C4 (AGRICULTURE APPLIC.) | FORD ESN-M2C134 C / D | SAUER SUNSTRAND/DANFOSS HYDRO STATIC TRANS FLUID |
| API CG-4 | FORD ESN-M2C159 B / C | ZF TE-ML 03A |
| API GL-4 | FORD FNH 82009203 | ZF TE-ML 05K |
| API GL-5 (LOW SPEED / HIGH TORQUE) | JD J20C | ZF TE-ML 06A |
| API SF / CE | JD J27 | ZF TE-ML 06B |
| CASE MAT 3525 | MF M 1135 | ZF TE-ML 06C |
| CASE MAT 3526 | MF M 1139 | ZF TE-ML 06C |
| DIN 51524 T3 HVLDPD | MF M 1143 | ZF TE-ML 07B |
| | MF M 1144 | ZF TE-ML 07D |
| | MF M 1145 | |

| GRADE | METHOD | UNIT | VALUE |
|------------------------------|------------|--------------------|-------|
| Density | ASTM D4052 | kg/l | 0,876 |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm ² /s | 103 |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm ² /s | 14,3 |
| Viscosity Index | ASTM D2270 | | 142 |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | 10,7 |
| Pour point | ASTM D6892 | °C | -33 |
| Flash point | ASTM D92 | °C | 222 |
| Sulphated ash content | ASTM D874 | % | |

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM