

# KHAYA UTTO 170 BM

UNIVERSAL TRACTOR TRANSMISSION OIL

**DYADE**  
LUBRICANTS

321100901



## UNIVERSAL TRACTOR TRANSMISSION OIL

This is a Universal Tractor Transmission Oil that has been developed to meet the Volvo BM quality standards. This product can be used in transmissions, lifters, rear axles and wet brakes of agriculture equipment and off-highway equipment. This product has been developed in order to extend product lifetime and have complete protection for the equipment.

## Product information

People buy this product because they need a UTTO oil that meets the requirements of Volvo BM

### CATEGORY

■ Agriculture Oils

### BASE OIL

■ Mineral

### AVAILABLE PACKAGING

■ 12x1 L

■ 5x4 L

■ 4x5 L

■ 20 L

■ 60 L

■ 205 L

■ 1000 L

## FUEL ECONOMY RATING

## SPECIFICATIONS

ALLISON C4	JD J20 C / D	ZF TE-ML 06E
API GL-4	KOMATSU KES 07.866	ZF TE-ML 06F
CASE MAT 3505	KUBOTA UDT	ZF TE-ML 06H
CASE MAT 3525	MF M 1127 / M 1129A	ZF TE-ML 06K
CASE MAT 3540	MF M 1135	ZF TE-ML 06M
CASE MS1206	MF M 1143	ZF TE-ML 06N
CASE MS1207	MF M 1145	ZF TE-ML 06P
CASE MS1209	NH NH 410B	ZF TE-ML 06R
CASE MS1210	VALTRA G2-08	ZF TE-ML 06S
CATERPILLAR MTO	VALTRA G2-B10	ZF TE-ML 06T
CATERPILLAR TO-2	VOLVO 97303 / WB101	ZF TE-ML 17E
FORD ESN-M2C-134 C / D	ZF TE-ML 03E	ZF TE-ML 21F
FORD ESN-M2C-86 A / B	ZF TE-ML 05F	
FORD ESN-M2C-86 C	ZF TE-ML 06B	
FORD FNHA-2-C-201.00	ZF TE-ML 06D	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,876
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	62,6
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	10,7
Viscosity Index	ASTM D2270		162
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,4
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	212
Sulphated ash content	ASTM D874	%	

All data on this technical data sheet is indicative only

202401V01



MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADE-LUBRICANTS.COM  
WWW.DYADEGLOBAL.COM